

Manufactured in the UK, to meet the demands of commercial kitchens around the world.

Precision's range of medium duty commercial under counter storage units are perfect for space optimisation in even the smallest of kitchens.

These durable, all stainless steel 150 litres Gastronorm Under Counters are available in refrigerated and deep freeze versions.

A 32°C ambient refrigeration system - managed by Precision's iCool energy saving controller - provides accurate temperature control and peace of mind 24 hours a day. Audio visual temperature alarms come as standard, along with HACCP capability.

The self contained refrigeration system comes with automatic defrost and our energy saving waste heat vaporiser system eliminating the need for a drain. Freezer models require manual defrost.

Refrigerators are available with a solid stainless steel door or a bank of 3 heavy duty drawers which are easily removed for cleaning.



Gastronorm Shelving

A lockable door, with removable magnetic balloon type gasket provides access to an adjustable Gastronorm 1/1 shelving system. Freezers are fitted with fixed refrigerated plate shelves.



refrigerator



deep freeze

Optional Features

Padlock facilities can be fitted to drawer models and a stacking kit is available to fix one unit on top of another. Extra shelves are available for refrigerator models.

Environmentally Friendly Insulation

precision Under Counters are all manufactured using Envirofoam. Not only is this environmentally friendly because it is based on renewable vegetable oils, but also because it requires less energy to produce than conventional petrochemical polyurethane foams.

General Specifications


32°C ambient refrigeration system
 iCool Energy saving controller with Alarms
 Automatic off cycle defrost (H)
 Manual defrost (L)
 Zero ODP injected polyurethane insulation
 Adjustable shelving system (H)
 Fixed plate shelves (L)
 Self closing door, with lock
 Removable magnetic door gasket
 Adjustable levelling feet - Front
 Rollers - Rear

Options


Extra shelves and clips
 Glass door & light (H)
 L / R hinge option
 Castors (adds 75mm to height)
 Stacking kit
 Helicoil cable

Temperatures


Refrigerators (H) 1 / 4 C
 Deep freeze storage (L) -18 / -22 C



PU 150



HPU 153



PU 150

Technical Data

model	temp. °C	nom. cap. litre	l mm	d mm	h mm	gas	shelves	ref. cap. watts	evap. @ °C	power	amps	wt. kg
UNDER COUNTER CABINETS												
HPU 150 SS	1 / 4 C	150	600	620	830	R134A	2	450	-5 C	240 / 50 / 1	1.5	75
HPU 153 SS	1 / 4 C	150	600	620	830	R134A	3*	450	-5 C	240 / 50 / 1	1.5	95
LPU 150 SS	-18 / -22 C	150	600	620	830	R134A	2*	500	-30 C	240 / 50 / 1	1.0	75

3* - HPU 153 fitted with 3 off drawers (non gastronorm)

2* - LPU 150 fitted with two fixed shelves